

TWO-POST GENERAL PURPOSE LIFTS

12K



EELR738A

Shown with optional adapter kit
EAK0299T29A



12K



LIFTING HEAVY LOADS ARE MADE EASIER WITH THE HOFMANN® 12K TWO-POST LIFT

The 12K Two-Post lift features include; symmetrical lifting, long reaching front and rear arms, adjustable insert screw lifting pads, padded overhead shut off bar and enhancing optional accessories

HEAVY-DUTY, TWO STAGE ARMS

- Enables heavy-duty, symmetric lifting up to 12,000 lbs (5,443 kg)

RUBBER DOOR GUARDS

- High quality rubber door guards provide added security against door damage

SINGLE POINT LOCK RELEASE

- Single point, mechanical lock release allow the technician to disengage both columns simultaneously

SCREW PADS

- Insert adjustable screw lifting pads with rubber contact surface for quick and easy vehicle set up

PREMIUM FINISH

- Premium powder coat finish provides a long lasting, durable finish

OVERHEAD SHUT OFF

- The padded overhead shut off system prevents vehicle damage from being raised too high

ADJUSTABLE COLUMN HEIGHT

- 13' 10" or 14' 7" adjustable column height accommodates higher profile vehicles and provides maximum headroom to work underneath vehicles

ANSI/ALI ALCTV:2011

- Independently Tested and Validated, ALI Certified to the current Automotive lift standard

AVAILABLE MODELS

12K Two-Post	EELR738A
--------------	----------

TECHNICAL SPECIFICATIONS

Capacity	12,000 lbs (5,443 kg)
Rise height	78.125" (198 cm)
Overall height - adjustable	166"/175" (422/445 cm)
Overall width	139.75" (355 cm)
Drive thru width	103" (262 cm)
Floor to overhead shut off	159.5"/168.5" (405-428 cm)
Front and Rear arm reach	35.75" - 54.5" (91 -139 cm)
Screw pad height	5.25" - 7.25" (13 - 18 cm)
Inside column width	115" (292 cm)
Ceiling height requirement	167" or 176" (424 - 447 cm)
Rise time	66 Seconds
Power requirements*	208-230V 1Ph 60Hz
Max load per arm	3,000 lbs (1,360 kg)

OPTIONAL ACCESSORIES

Extension Adapter Kit Includes: Four 3" stack extensions, two 6" stack extension and two organizer brackets with mounting hardware	EAK0299T22A
Organizer rack for stack adapter extensions	EAK0299T52A
Two 6" stack adapter extensions	EAK0299T23A
Air/Electric workstation with filter/ lubrication/regulator	EAK0299T27A
Four u-shaped frame truck adapters [†]	EAK0299T25A
Two u-shaped frame truck adapters	EAK0299T24A
24" blue height extension	EAK0299T44A
Adapter kit (includes EAK0299T22A and EAK0299T25A)	EAK0299T29A

*Optional three phase electrical also available, specify at time of order

[†]Frame engaging adapters are required when lifting vehicles with frame construction

For more information regarding the 12K Two-Post Lift, call 800.251.4500 (US) or 501.505.2662 (Canada) www.hofmann-usa.com / www.hofmann.ca

Hofmann is committed to product innovation and improvement. Therefore, specifications listed in this sheet piece may change without notice. ©2016 Snap-on Incorporated. Hofmann is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. 05/16 SS143421A

