

TWO-POST GENERAL PURPOSE LIFTS

# 18K



EELR741A



18K



## LIFTING HEAVY LOADS ARE MADE EASIER WITH THE HOFMANN® 18K TWO-POST LIFT

Hofmann announces the release of its tested tough 18,000 lb heavy duty capacity twin post models. The twin post models have many unique features such as the adjustable stacking screw pad system, included standard adapters and extra-long lifting carriages to optimize load distribution and providing smooth operation. Standard height and Extended height models available.

### SINGLE POINT LOCK RELEASE

- Single point, air actuated lock release allows the technician to disengage both of the columns simultaneously

### OVERSIZED STEEL PULLEY SYSTEM

- Oversized, steel pulleys reduce the stress on the equalization system and provide increased durability

### LIFTING CARRIAGE

- 60" (152.4 cm) lifting carriage lessens stress on the column by dispersing the load

### SCREW PADS

- Standard combination stack screw pads and storage brackets accommodate the technician with a wide range of vehicle pick-up points

### OVERHEAD SHUT OFF

- The padded overhead shut off system prevents vehicle damage from being raised too high

### ANSI/ALI ALCTV:2011

- Independently Tested and Validated, ALI Certified to the current Automotive lift standard

### AVAILABLE MODELS

<b>18K Two-Post (Standard Height)</b>	EELR741A
<b>18K Two-Post (Extended Height)</b>	EELR742A

### TECHNICAL SPECIFICATIONS

<b>Capacity</b>	18,000 lbs (8,164 kg)
<b>Rise height*</b>	85" (216 cm)
<b>Overall height</b>	EELR741A: 174" (442 cm) EELR742A: 198" (502.9 cm)
<b>Overall width</b>	154.75" (393.1 cm)
<b>Drive thru width</b>	104.25" (264.8 cm)
<b>Floor to overhead shut off</b>	EELR741A: 167" (424.2 cm) EELR742A: 191" (485.1 cm)
<b>Front and Rear arm reach</b>	38.5" - 62" (97.8 - 157.5 cm)
<b>Screw pad height</b>	6.625" - 8" (16.8 - 20.3 cm)
<b>Inside column width</b>	119.875" (304.5 cm)
<b>Ceiling height requirement</b>	EELR741A: 176" (447 cm) EELR742A: 200" (508 cm)
<b>Rise time</b>	60 Seconds
<b>Power requirements**</b>	208-230V 1Ph 60Hz
<b>Max load per arm</b>	4,500 lbs (2,041 kg)

### STANDARD ACCESSORIES

Four u-shaped frame truck adapters	Organizer rack for stack adapter extensions
Four reducer bushings for use with u-shaped frame truck adapters	Four medium and two extended height adapters; 4" (10.1cm) and 8" (20.3cm)

### OPTIONAL ACCESSORIES

<b>Air/Electric workstation with filter/lubrications/regulator</b>	EAK0299T27A
<b>24" (61 cm) Height extension†</b>	EAK0299T48A

\*Rise height is measured with high extension

\*\*Optional three phase electrical also available, specify at time of order

†Only available for EELR741A

For more information regarding the **18K Two-Post Lift**, call **800.251.4500 (US)** or **501.505.2662 (Canada)**  
[www.hofmann-usa.com](http://www.hofmann-usa.com) / [www.hofmann.ca](http://www.hofmann.ca)

Hofmann is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet piece may change without notice. ©2016 Snap-on Incorporated. Hofmann is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders.

05/16 SS143423A

