

HIGH-VOLUME TIRE CHANGERS

monty®

TIRE CHANGING SYSTEMS

3300



HOFMANN® 

3300



INNOVATIVE TIRE CHANGER FOR HIGH-VOLUME SHOPS

The Hofmann® *monty* 3300 and 3300em high-performance tire changers are designed for high-volume tire shops, multi-bay repair shops and car dealerships. Technicians can effortlessly & safely change standard tires or the most difficult performance tires (low-profile and run flat-tires) on cars, SUVs and light trucks. The *monty* 3300 series feature a powerful, multi-position bead breaker that delivers 6,000 lbs of power at the bead shovel, making easy jobs of both the stiffest and softest sidewalls.

ACCOMMODATES LARGE WHEEL & TIRE ASSEMBLIES

- Allowing for a tire diameter of 40" and an outer-wheel diameter of 24" on the *monty* 3300/3300em can handle wheel and tire assemblies found on cars and light trucks

DUAL WHEEL CLAMPING CYLINDERS

- Dual pneumatic clamping cylinders control all four clamping jaws, eliminating damage to wheel due to slippage

MULTI-POSITION BEAD BREAKER

- 6,000 lbs of power at the bead shovel and a range of up to 17" wide. The two-stage pneumatic cylinder provides precise power and can be toggled with the foot pedal as needed

POWERFUL TIRE INFLATION SYSTEM

- Powerful air blast operated by the foot pedal. Each moveable jaw is precisely set to the exact position under the wheel to seal the tire bead

BUILT TO LAST

- Heavy, solid half inch thick steel clamping table. Rugged steel reinforced chassis. Rust proof air cylinders and valve. On-board compressed air lubricator and regulator

UPGRADEABLE

- EasyMont Pro* features a three-piece design with a top roller, pressing foot and lifting disc. Each piece provides a specialized function that assists a single operator in mounting/demounting low-profile and high-performance tires

AVAILABLE MODELS

<i>monty</i> 3300em	M3300110EM
<i>monty</i> 3300	M3300110

TECHNICAL SPECIFICATIONS

Overall wheel clamping diameter	10" - 24" (25 - 61 cm)
Inner wheel clamping diameter	12" - 24" (30.5 - 61 cm)
Outer wheel clamping diameter	10" - 24" (25 - 61 cm)
Bead breaker range	2" - 17" (5 - 43 cm)
Bead loosening power	6,000 lbs (2,722 kg)
Maximum outer tire diameter	40" (101.6cm)
Shipping weight (<i>monty</i> 3300em)	855 lbs (387.8 kg)
Shipping weight (<i>monty</i> 3300)	625 (283.5 cm)
Power requirements	120V 1Ph 60Hz

OPTIONAL ACCESSORIES

EasyMont Pro bead assist device*	EAA0329G35B
Motorcycle/ATV adapters	EAA0329G53A
Quick change bead head kit*	EAA0304G66A
Composite mount/demount head	EAA0247G20A
Outside clamping jaw protectors	EAK0237J19A
Snap-in jaw protector	EAC0087G48A
Protective cover for bead breaker shovel*	EAA0304G15A
Replacement composite head	EAM0043G71A
Wave tire tool	EAA0304G14A
Bead pusher	EAA0377G23A
Hex bar with roller attachment	EAA0329G92A
Bead breaker disc	EAA0304G43A
Bead clamp for performance wheels	EAA0247G70A
Bead clamp for run-flat tires	EAA0247G11A
Protective slide cover	ST0029455
Premium tire paste	8-03229A

*Standard with *monty*® 3300em models. Optional for *monty*® 3300

For more information regarding the *monty*® 3300,
call 800.251.4500 (US) or 501.505.2662 (Canada)
www.hofmann-usa.com / www.hofmann.ca

Hofmann is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet page may change without notice. ©2016 Snap-on Incorporated. Hofmann is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders.
08/16 SS2706D

